



# Introduction

Name: ZL-2720 QDS-15KV Enameled Wire Voltage Tester



•Implementation standard: IEC60851-5.

Tel: [+86-769-88055358](tel:+86-769-88055358)

Fax: [+86-769-88055357](tel:+86-769-88055357)

Website: [www.zltester.com](http://www.zltester.com)

E-mail: [Zhongli@zltester.com](mailto:Zhongli@zltester.com)

Address: [Room 722, Dongyuan Mansion, No.159 QiFeng Road, Dongguang city,P.R.C](#)



- It is provided with three voltage-rising speeds: 20V/S, 100V/S, and 500V/S
- It can test five samples at one time
- LED can display test results, and return to zero position automatically
- When the sample is cut through, its voltage will keep displaying for from 2 to 10 seconds (adjustable), which will make the testing results clear and distinguishable
- It is equipped with testing clamps and poises for round stick method and wring method
- Safety precautions of this tester are in line with relevant provisions of high voltage test equipments, and its door has safe interlock
- It also can be applied to withstand voltage test.

Models for your choice: QDS-20KV Enameled Wire Voltage Tester;

QDS-15KV-B Enameled Wire Voltage Tester  
(single electrode)

|                                       |                         |
|---------------------------------------|-------------------------|
| Cutting-through Current               | 5±0.5mA                 |
| Highest Testing Voltage               | ≥15000V                 |
| Error of Voltage Displayed            | <2%                     |
| Rated Capacity of Testing Transformer | 1000VA                  |
| Diameter of Round Stick's Electrode   | 25±0.5mm                |
| Time of Voltage Withstand             | 1s~99min99s preset      |
| Work Environment                      | Temperature: 0~40℃      |
|                                       | Relative humidity: ≤85% |
| Input Power Supply                    | AC220V±5% 50Hz          |
| Consumed Power                        | ≤1200W                  |
| Dimension                             | L×W×H 550×600×1700mm    |
| Weight                                | 120Kg                   |

Tel: [+86-769-88055358](tel:+86-769-88055358)

Fax: [+86-769-88055357](tel:+86-769-88055357)

Website: [www.zltester.com](http://www.zltester.com)

E-mail: [Zhongli@zltester.com](mailto:Zhongli@zltester.com)

Address: [Room 722, Dongyuan Mansion, No.159 QiFeng Road, Dongguang city,P.R.C](#)



东莞中力仪器科技有限公司

ZhongLi Instrument Technology Co., Ltd.

---

Tel: [+86-769-88055358](tel:+86-769-88055358)

Fax: [+86-769-88055357](tel:+86-769-88055357)

Website: [www.zltester.com](http://www.zltester.com)

E-mail: [Zhongli@zltester.com](mailto:Zhongli@zltester.com)

Address: [Room 722, Dongyuan Mansion, No.159 QiFeng Road, Dongguang city,P.R.C](#)